

Specialty Chemical Manufacturers for Industry, Biosecurity and Aviation

CALGUARD ANTI-SPATTER SPRAY

Code 1400
Waterbased Weld-Spatter Agent

DESCRIPTION

Calguard Anti-Spatter Spray is a water based, paintable, cost effective and non-flammable agent for the prevention of weld-spatter adhering to metal surfaces during the welding process.

Calguard Anti-Spatter Spray has outstanding performance preventing spatter sticking to a wide range of steels, including mild steel, stainless, steels and aluminium.

Calguard Anti-Spatter Spray avoids the need for mechanical abrasion or grinding of weld spatter following welding. It contains corrosion inhibitors for base metal protection. Calguard increases the life of torch components saving time and money. Eliminates spatter build up which results in poor gas flow causing pitting, porosity and burnbacks.

PHYSICAL PROPERTIES

Appearance : Light red mixes freely with water
Boiling Point (Deg C) : 100° C
Specific Gravity : 1.008

BENEFITS

Reduces downtime for cleanup tasks	Non-toxic, biodegradable
No-flammable	Ozone safe
Uniform spray with no bubbles	Paintable , contains no silicones
User safe	Eliminates need for grinding unwanted spatter
Economical	Base metal corrosion protection

DIRECTIONS FOR USE

Welding Torch

Spray Calguard Anti-Spatter Spray before welding in a thin and uniform film onto the areas to be protected. Hold spray can approximately 30 cm from the surface to be protected. Also use the spray to protect the interior and exterior of nozzles, the end and outer surface of contact tips, and all other potential areas which are subject to weld spatter. It may be advisable to spray diffusers and the base of the nozzle support as well.

Base Metal

Spray Calguard Anti-Spatter Spray hold spray can approximately 30cm from surface to be protected. Spray a thin uniform coating. Do not over apply solution as excessive solution application may be detrimental to the weld quality.

Application Methods

Hand held spray applicator for welding torch components and base metal areas. Wiping and mopping may be used for base metal large areas.

Specialty Chemical Manufacturers for Industry, Biosecurity and Aviation

Calguard Anti-Spatter Spray (1400) - Page 2 of 2

NOTE

To remove Calguard Anti-Spatter Spray after use, clean the surface with Prosol Solvent Degreaser or equivalent steel compatible degreaser.

CAUTION

Avoid contact with eyes. Used in a well ventilated area. Avoid prolonged skin contact (>24 hours).

OTHER CALLINGTON METAL TREATMENT PRODUCTS:

S-Weld Clean Pickling Gel	:	For removal of weld scale from stainless steel & high performance alloys.
S-Weld Neutraliser	:	For the neutralising of acidic pickling waste.
S-Weld Passivator	:	An oxidising agent for passivation of stainless steel & high performance alloys.
Prosol Cleaner & Degreaser	:	All purpose metals & cleaner.
Metaprep No.1	:	Metal deoxidiser & cleaner.
Alu-Weld Gel	:	Aluminium weld scale remover & brightener.
Albright	:	Aluminium brightener & cleaner.

PACKAGING

Calguard Anti-Spatter spray is available in 750ml, 5 litre or 20 litre drums.

WARRANTY – All statements, information and data presented herein are believed to be accuracy and reliable but are not to be taken as a guarantee, expressed or implied, for which seller assumes legal responsibility and they are offered solely for your consideration, investigation and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent.
10 October 2008



CALLINGTON HAVEN PTY LTD
Incorporated in New South Wales
ACN 000 632 404 ABN 28 000 632 404
30 South Street Rydalmere NSW 2116
PO Box 144 Rydalmere NSW BC 1701 Australia
T: (61-2) 9898 2788 F: 9684 4215
E: enquiries@calhaven.com.au W: www.callingtonhaven.com

